


Choose Your Slot Die Applicator Comparison Chart

Slot Die Applicator


**BF
Slot Die**



**Equity
Slot Die**




**APEX
Slot Die**



**CrossCoat Fluid
Extrusion Die
(Curtain)**



Twin Coat



**Vector Metered
Slot Die**



Contact vs. Non-Contact	Contact	Contact	Contact	Non-Contact	Non-Contact	Contact
Operating Temperature	38°C to 218°C (100°F to 425°F)	38°C to 218°C (100°F to 425°F)	38°C to 218°C (100°F to 425°F)	38°C to 200°C (100°F to 392°F)	38°C to 200°C (100°F to 392°F)	38°C to 218°C (100°F to 425°F)
Adhesive Viscosity	20,000 cps	100 to 40,000 cps	100 to 20,000 cps	1,000 to 200,000 cps*	1,000 to 200,000 cps	500 to 30,000 cps*
Application Type	Continuous	Continuous	Continuous / Intermittent	Continuous	Continuous	Continuous / Intermittent
Max. Coating Width	900 mm (35.43 in)	900 mm (35.43 in)	460 mm (18.11 in)	3,000 mm (118 in)	2,700 mm (106 in)	550 mm (21.7 in)
Coat Weight Minimum	.5 mil	.5 mil	.5 mil	.5 mil	.5 mil	.5 mil
Cross-Web Accuracy	± 10%	± 10%	± 10%	± 3%	± 3%	± 0.5%
Supply Voltage	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz	200-240 VAC 1 Phase 50-60Hz
Dimensions (HxDxW)	99 x 100.5 x 44mm (3.9 x 3.95 x 1.73 in)	335 x 150 x 130-930 mm (13.2 x 5.9 x 5.1-36.6 in)	241 x 93 x 50-510 mm (9.5 x 3.6 x 1.9-20 in)	Custom	Custom	362 x 93 x 100-600 mm (14.25 x 3.6 x 3.9-23.6 in)

Note: All above information is dependent on line speed operation and type of adhesive, some results may vary.

* Adhesive dependent