

# DG II™

THE DG II™ HOT MELT HAND APPLICATORS ROBUST DESIGN & RELIABLE PERFORMANCE MAKE IT IDEAL FOR MANUALLY DISPENSING ADHESIVE IN A VARIETY OF PATTERNS.

## **FLEXIBILITY**

Rotary swivel or ball swivel with top or bottom hose connection.

## **SAFETY**

Ergonomic handle with a clear sight line to the nozzle tip.

## **DURABILITY**

Rugged and durable glass-filled nylon construction.



## DG II™ HOT MELT HAND APPLICATOR

The DG II™ is designed for durability and flexibility. Adhesive output may be oriented for straight or right angle application with a variety of available bead and spiral spray nozzles. The DG II™ applicator can be set up for bottom-entry or top-entry hose connection.

### FEATURES

- Rotary or ball swivel with top or bottom hose connection.
- Ergonomic handle with a clear sight line to the nozzle tip.
- Easy to change cartridge-style heater and sensor.
- Four-finger trigger with built-in trigger lock.
- Straight or right angle nozzle adapter.
- Bead or swirl applications.

### OPTIONS

- The rotary swivel is useful when the hose is connected at the bottom of the hand applicator. The movement of the applicator can control the hose position.
- The ball swivel is useful when the hose is connected at the top of the hand applicator and the applicator is suspended from the hose or a tool balancer.
- Two-finger trigger configurations available.
- Right angle bead and swirl nozzle configuration available.
- Electrical: 80Watts at 120 or 240VAC 1 Phase 50/60Hz

### TECHNICAL DATA

Operating temperature range	38° to 232°C (100° to 450°F)
Viscosity range	0 - 80,000 cps
Pneumatic pressure range to solenoid	.48 - .96 MPa (70 - 140 psi) (for swirl application only)
Supply voltage setup 1	120 VAC 60 Hz
Supply voltage setup 2	240 VAC 50 Hz
Height	22.2 cm (8.74 in)
Depth	22.5 cm (8.46 in)
Width	4.2 cm (1.65 in)

### LOCATIONS

#### Americas

ITW Dynatec  
31 Volunteers Drive  
Hendersonville, TN 37075  
Phone: +1.615.824.3634  
Fax: +1.615.264.5248  
info@itwdynatec.com  
www.itwdynatec.com

#### China

ITW Dynatec Suzhou  
No.2 Anzhi Street  
SIP, Suzhou, 215122 China  
Phone +86.512.6289.0620  
Fax +86.512.6289.0621  
info@itwdynatec.cn  
www.itwdynatec.cn

#### Japan

ITW Dynatec K.K.  
Flos Kamata  
26-11, Nishikamata 7-chome  
Ota-ku, Tokyo 144-0051, Japan  
Phone: +81.3.5703.5501  
Fax: +81.3.5703.5505  
info@itwdynatec.co.jp  
www.jp.itwdynatec.com

#### Europe, Middle East and Africa

ITW Dynatec GmbH  
Industriestraße 28  
40822 Mettmann, Germany  
Phone: +49.2104.915.0  
Fax: +49.2104.915.111  
info@itwdynatec.de  
www.itwdynatec.de

